


### 787TC ISO 18752-DC



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 77 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	
787TC-8	1/2	12,5	0.83	21,1	5000	35,0	3-1/2	90	0.45	0,67	•
787TC-10	5/8	16	0.94	23,9	5000	35,0	4	100	0.54	0,80	•
787TC-12	3/4	19	1.10	27,9	5000	35,0	4-3/4	120	0.78	1,16	•
787TC-16	1	25	1.40	35,7	5000	35,0	6	150	1.17	1,74	•

**Application:** Petroleum base hydraulic fluids and lubricating oils.

**Inner Tube:** Proprietary synthetic rubber.

**Reinforcement:** Four spiral steel wire

**Cover:** Synthetic rubber, MSHA accepted.

**Temperature Range:**

-40°C to 125°C  
(-40°F to 257°F)

### 797TC ISO 18752-DC



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 77 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	
797TC-8	1/2	12,5	0.83	21,1	6000	42,0	4	100	0.45	0,67	•
797TC-10	5/8	16	0.94	23,9	6000	42,0	4-1/2	115	0.54	0,80	•
797TC-12	3/4	19	1.10	27,9	6000	42,0	5-1/4	135	0.78	1,16	•
797TC-16	1	25	1.40	35,7	6000	42,0	6-1/2	165	1.17	1,74	•

**Application:** Petroleum base hydraulic fluids and lubricating oils.

**Inner Tube:** Proprietary synthetic rubber.

**Reinforcement:** Four spiral steel wire

**Cover:** Synthetic rubber, MSHA accepted.

**Temperature Range:**

-40°C to 125°C  
(-40°F to 257°F)